

# International Journal of Scientific and Engineering Research



[Home](#)

[About](#)

[Publication Indexing](#)

[Latest News](#)

**Call For Papers**

[Call For Papers 2014](#)

[Online Submission](#)

[Research Paper](#)

[Status](#)

**Authors**

[Authors GuideLines](#)

[Publication Charge](#)

[Registration](#)

[Certificate Request](#)

[Thesis Publication](#)

[How to publish](#)

[research paper](#)

[Research Paper](#)

[Topics](#)

[FAQs](#)

**Editors**

[Editorial Board](#)

[Editorials](#)

**Thesis**

**Publication**

[2013-2014 List of](#)

[Thesis](#)

[Online Thesis](#)

[Submission](#)

[Thesis Publication](#)

[Detail](#)

**Current**

**Publications**

**2014 Edition**

[January 2014](#)

---

**Volume 5, Issue 9, September 2014 Edition**

 [Register for IJSER Research Forum](#)  
[Paper Database](#)

 [IJSER Xplore Research](#)

---

**Pages** [\[1\]](#) [\[2\]](#) [\[3\]](#) [\[4\]](#) [\[5\]](#) [\[6\]](#) ...[\[11\]](#)



---

**Clustering Algorithm Combined with Empirical Mode  
Decomposition for Classification of Remote Sensing Image**[\[Full-Text \]](#)  
**B.Sai Chandana, Dr.K.Srinivas, Dr.R.Kiran Kumar**

Clustering is an unsupervised classification method widely used for classification of remote sensing images. As the spatial resolution of remote sensing images getting higher and higher, the complex structure is the simple objects becomes obvious, which makes the classification algorithm based on pixels being losing their advantages. In this paper, four different clustering algorithms such as K-means, Moving K-means, Fuzzy K-means and Fuzzy Moving K-means are used for classification of remote sensing images. In all the traditional clustering algorithms, number of clusters and initial centroids are randomly selected and often specified by the user. In this paper, the estimation of number of clusters and initial centroids using Empirical Mode Decomposition algorithm (ECEMD) for the histogram of the input image will generate the number of clusters and initial centroids required for clustering. It overcomes the shortage of random initialization in traditional clustering and achieves high computational speed by reducing the number of iterations. The experimental results show that Fuzzy Moving K-means has classified the remote sensing image more accurately than other three algorithms.

---

---